

# TIMBERCOAT

## TIMBERCOAT MATT CLEAR SD-156

**TYPE** Based on non drying short oil length resin, nitrocellulose, additives, solvents and very special type of effect additive

**RECOMMENDED USE** This clear shows very smooth matt effect appearance when applied on dull sealed/coated wooden articles. Matt uniformly is very good when applied on any kind of wooden articles followed by sealer

### PRODUCT DATA

<b>SPECIFIC GRAVITY</b>	0.97 ± 0.02Kg/Ltr.	<b>% NVM</b>	37.00 +/- 2%
<b>VISCOSITY/ FCB#4/30°C</b>	60 Sec ± 5	<b>FLASH POINT</b>	27°C
<b>FINISH</b>	Smooth and bits free		

### SURFACE PREPARATION

Clean the substrate after sanding with emery paper. Apply coatings at a regular interval of 3 to 4 minutes and build up coating thickness for mattness

**DRYING TIME AT 30°C**  
 Surface Dry : 10 Min. max  
 Tack free Dry : 30 Min. max  
 Hard Dry : Overnight

### APPLICATION DATA

#### APPLICATION BY



Spray

### PERFORMANCE DATA

**ADHESION** Excellent on wooden surface

**GLOSS at 60°** 5 - 7unit, Matt

#### PACKING

