

TIMBERCOAT

TIMBERCOAT SANDING SEALER

TYPE Based on Nitrocellulose & short oil length nondrying alkyd resins, Sanding aid, filler, additive & thinner combination

RECOMMENDED USE This Sanding Sealer is specially designed formulation where wood grains & dents fill very well and give better Sanding property with smooth surface of wood for top coat of Furniture, Kitchen trays, Shelf, Musical instruments etc. It improves longevity of wooden article and enhance their durability.

PRODUCT DATA

SPECIFIC GRAVITY	0.94 ± 0.02kg/ltr	% NVM	28.00 +/- 2%
VISCOSITY/ FCB#4/30°C	28 ± 2 Sec	FLASH POINT	27°C
FINISH	Smooth and bits free	COLOUR	Haze white

SURFACE PREPARATION

Clean the substrate after sanding with emery paper. apply coatings at a regular interval of 3 to 4 minutes and build up coating thickness for Mattness

DRYING TIME AT 30°C
 Surface Dry: 10 min max
 Tack free Dry: 30 min max
 Hard Dry: Overnight

APPLICATION DATA

APPLICATION BY



Spray



Putty Knife

PERFORMANCE DATA

ADHESION Excellent on wooden surface

SANDING AFTER 4 HRS. Excellent

PACKING

