

TIMBERCOAT

TIMBERCOAT WOOD GUARD CLEAR

TYPE Based on non drying short oil length resin, nitrocellulose, additives, solvents and special type effect additives

RECOMMENDED USE It is a glossy clear to be applied on wooden surface by hand ragging or by spraying. It may be applied directly on wooden surface, metal surface, coil board, etc. It has high bonding strength to the substrate.

PRODUCT DATA

COLOUR	Clear transparent liquid	VISCOSITY/ FCB#4/30°C	90 ± 5 seconds
SPECIFIC GRAVITY	0.96 ± 0.02	% NVM	36.00 +/- 2%

SURFACE PREPARATION

Clean the substrate after sanding with emery paper. Apply coating at a regular interval of 3 to 4 minutes and build up coating thickness for gloss

DRYING TIME AT 30°C
 Surface dry: 10 min max
 Tack Free Dry: 30 min max
 Hard dry: overnight

APPLICATION DATA

APPLICATION BY



Spray

By spray or by cloth ragging

DILUTION

30% to 40% with NCT -2

PERFORMANCE DATA

ADHESION Excellent on wooden surface

**GLOSS at 60°
(On Metal Surface)** 90 Unit minimum.

PACKING



4 Ltr.



20 Ltr.