

Es Q PRIMER

Es Q PRIMER is an acrylic based primer designed for interiors. Primer offers excellent penetration and hence the bonding over various surfaces.



IDEAL FOR Interior Cement/ Gypsum Plaster, Gypsum Board, Concrete Surfaces

- BENEFITS**
- Low VOC - A Green Concept Product
 - Good Bonding
 - Excellent Durability

COLOUR White

FINISH Smooth

SURFACE PREPARATION Ensure that the surface to be painted is perfectly cured, dry, free from curing compounds, cracks, contamination, moisture and, is perfectly levelled. Ensure that there is no water/dampness within the substrate to be painted. Plastered surface should ideally be abraded using putty knife so as to remove the loosely bonded sand particles followed by cleaning. For concrete, it is advised to remove the laitance using mechanical wire brush. Old weak paint if any must be removed by scraping. Ensure that the surface to be painted is dust free, dry and clean.

TREATMENT OF CRACKS Open the cracks in 'V' shape using mechanical cutter and clean well. Apply primer using brush and allow it to dry as recommended. Fill the cracks using CIVILTECH CRACKGARD, repeat application if required.


RECOMMENDED DILUTION Stir the paint well. Dilute the paint using potable water at the ratio 1 Ltr paint + 500 ml water



APPLICATION BY



OVERCOATING TIME



TYPICAL RECOMMENDED PAINT SYSTEM

1 x coat **Es Q PRIMER (INT)**
 2 x coats PREMIUM ACRYLIC PUTTY (as required)
 2 x coats Es Q SUPER PREMIUM/CLASSIC/BASIX
 (In case of Cement Putty applied surface, follow the same system as above but in this case, Acrylic Putty would be required as touch up only. For a better finish, apply a coat of primer by roller after Acrylic Putty)

INDICATIVE COVERAGE **120 - 140 Sq.ft./Ltr/Coatt :**
 (As the coverage depends upon several factors, we advise to confirm the coverage by actual application over desired surface)

PRECAUTIONS Stir the can well before use. Do not apply when ambient temperature is below 10 °C or if the temperature drops to that level within next 4 hrs. from the time of application. In order to get effective performance, avoid application during high humidity, rainy and dusty weather conditions.

SAFETY FEATURES



Store the airtight container in a cool, dry and covered place away from sunlight. Keep it away from children and eatables. Do not swallow. Get medical attention immediately if swallowed. Protect eyes during handling, application etc. In case of eye or skin contact, rinse the eyes immediately with potable water and remove the paint over skin using soap and water. Wear suitable masks to avoid inhaling. Do not spill the paint in drain or in water bodies.

SHELF LIFE 3 years if kept in original airtight container in upright position in a covered dry place.

PACKING



ESDEE PAINTS LTD.
 203, Navketan, C.A. Road, Chembur,
 Mumbai - 400071 (INDIA)

CUSTOMER CARE
 Tel: 022 - 25893780
 E mail : info@esdeepaints.com | customercare@esdeepaints.com