

PRIMIN

PRIMIN is a penetrating primer for interiors providing good durability.



IDEAL FOR

Interior Cement /Gypsum Plaster, Gypsum Board, Concrete Surface

BENEFITS

- A Green Concept Product
- Good durability
- Good penetration
- Low VOC product
- Improved finish
- Good opacity

COLOUR

White

FINISH

Smooth


SURFACE PREPARATION

Ensure that the surface to be painted is perfectly cured, dry, free from curing compounds, cracks, contamination, moisture and, is perfectly levelled. Please ensure that there is no water/dampness within the substrate to be painted. Plastered surface should ideally be abraded using putty knife so as to remove the loosely bonded sand particles followed by cleaning. For concrete, it is advised to remove the laitance using mechanical wire brush. Old weak paint if any must be removed by scraping. Ensure that the surface to be painted is dust free, dry and clean.

TREATMENT OF CRACKS

Open the cracks in 'V' shape using mechanical cutter and clean well. Apply primer using brush and allow it to dry as recommended. Fill the cracks using appropriate Crack Filler, repeat application if required.

RECOMMENDED DILUTION Stir the paint well. Dilute the paint using potable water at the ratio 1 Ltr paint + 500 ml water



APPLICATION BY



OVERCOATING TIME



4 - 6 hrs.
at 30 °C

TYPICAL RECOMMENDED PAINT SYSTEM

1 x coat PRIMIN
2 x coats PREMIUM ACRYLIC PUTTY
2 x coats ECOSILK/HARMONY/SWAGAT/ESPRO range
(for a better finish, a coat of primer by roller after 2nd coat putty is advisable)

INDICATIVE COVERAGE

120 - 140 Sq.ft./Ltr/Coat
(As the coverage depends upon several factors, we advise to confirm the coverage by actual application over desired surface)

PRECAUTIONS

Stir the can well before use. Do not apply when ambient temperature is below 10 °C or if the temperature drops to that level within next 4 hrs. from the time of application. In order to get effective performance, avoid application during high humidity, rainy and dusty weather conditions.

SAFETY FEATURES



Store the airtight container in a cool, dry and covered place away from sunlight. Keep it away from children and eatables. Do not swallow. Get medical attention immediately if swallowed, . Protect eyes during handling, application etc. In case of eye or skin contact, rinse the eyes immediately with potable water and remove the paint over skin using soap and water. Wear suitable masks to avoid inhaling. Do not spill the paint in drain or in water bodies.

SHELF LIFE

3 years if kept in original airtight container in upright position in a covered dry place.

PACKING



ESDEE PAINTS LTD.

203, Navketan, C.A. Road, Chembur,
Mumbai - 400071 (INDIA)

CUSTOMER CARE

Tel: 022 - 25893780

E mail : info@esdeepaints.com | customercare@esdeepaints.com