

SHEENMAX

Interior - Exterior High Sheen Emulsion



www.esdeepaints.com

SHEENMAX

SHEENMAX is a very unique and specialised high sheen product designed to be used for interiors and exteriors. Perfect blend of acrylic binder and quality pigments delivers resistance against water, UV, humidity etc. which helps in offering excellent performance properties and hence the durability. Product when used exteriors, offers good resistance to algae. When used over interior walls, SHEENMAX would offer a very fine and smooth finish.



IDEAL FOR Interior Cement /Gypsum Plaster, Gypsum Board, Concrete Surfaces, Exterior Cement Plaster/Concrete


- BENEFITS**
- Low VOC - A Green Concept Product
 - All season product
 - Algae, water, humidity resistant
 - Rich finish
 - Excellent durability
 - Wide range of colours
 - Washable, Very attractive sheen

COLOUR As per Shade card and fandek **FINISH** Smooth with high sheen

SURFACE PREPARATION Ensure that the surface to be painted is perfectly cured, dry, free from any cracks, contamination, moisture, algae, fungus etc. For Interiors, surface should ideally be prepared using PRIMIN PLUS/PRIMIN followed by PREMIUM ACRYLIC PUTTY followed by a coat of PRIMIN PLUS/PRIMIN. For exterior concrete, surface should ideally be prepared using mechanical wire brush and for plastered surface, manual sanding should be done followed by cleaning and followed by a coat of PRIMEX PLUS/PRIMEX. Clean the surface well before top coat application.

TREATMENT OF CRACKS Open the cracks in 'V' shape using mechanical cutter and clean well. Apply primer using brush and allow it to dry as recommended. Fill the cracks using appropriate Crack Filler, repeat application if required.


RECOMMENDED DILUTION Stir the paint well. Dilute the paint using potable water at the ratio 1 Ltr paint + 500 ml water.



APPLICATION BY



OVERCOATING TIME



4 - 6 hrs.
at 30 °C

TYPICAL RECOMMENDED PAINT SYSTEM

For INTERIORS
1 x coat PRIMIN PLUS/PRIMIN 2 x coats PREMIUM ACRYLIC PUTTY 2 x coats **SHEEN MAX** (for a better finish, a coat of primer by roller after 2nd coat putt is advisable)

For EXTERIORS
1 x coat PRIMEX PLUS/PRIMEX 2 x coats SHEEN MAX (for a better protection, additional coat of **SHEEN MAX** is recommended over horizontal surfaces.

INDICATIVE COVERAGE Interiors: 130 - 160 Sq.ft./Ltr/Coat
Exteriors: 100 - 110 Sq.ft./Ltr/Coat
(As the coverage depends upon several factors, we advise to confirm the coverage by actual application over desired surface)

PRECAUTIONS Stir the can well before use. Do not apply when ambient temperature is below 10 °C or if the temperature drops to that level within next 4 hrs. from the time of application. In order to get effective performance, avoid application during high humidity, rainy and dusty weather conditions. For better performance, use the diluted paint within 24 hrs.

SAFETY FEATURES



Store the airtight container in a cool, dry and covered place away from sunlight. Keep it away from children and eatables. Do not swallow. Get medical attention immediately if swallowed. Protect eyes during handling, application etc. In case of eye or skin contact, rinse the eyes immediately with potable water and remove the paint over skin using soap and water. Wear suitable masks to avoid inhaling. Do not spill the paint in drain or in water bodies.

SHELF LIFE 3 years if kept in original airtight container in upright position in a covered place.

PACKING

